



Specifications Van Amerongen CO₂ scrubbers

Type	Capacity (kg CO ₂ 24 h ⁻¹ at 3%)	Voltage (VAC)	Current (Amps)	Power (kW)	Plug	Noice level (dB)	Dimensions (W x D x H, meter)			Weight (kg)	PVC connection (mm)	Content ,lung' (m ³)
VA50	50	230	4,0	1,1	16 A, 2 poles	75	1,15	1,10	1,80	200	75/50	2
VA100	70	230	4,0	1,1	16 A, 2 poles	75	1,15	1,15	1,80	300	75/50	3
VA150	100	230	4,0	1,1	16 A, 2 poles	75	1,15	1,35	1,80	655	75/50	3
VA200	150	230	5,0	1,1	16 A, 2 poles	75	1,15	1,45	1,80	775	125	4
VA350	200	230	5,0	1,1	16 A, 2 poles	75	1,15	1,55	1,95	840	125	6
VA500	250	400	4,0	2,6	16 A, 5 poles	78	1,15	1,70	2,20	1.150	125	10
VA600	325	400	4,0	2,6	16 A, 5 poles	78	1,15	1,70	2,20	1.275	125	10
VA900	450	400	5,0	2,6	16 A, 5 poles	78	1,20	1,80	2,20	1.330	125	10
VA1000	550	400	5,0	3,1	16 A, 5 poles	78	1,25	1,85	2,20	1.440	125	10
VA1200	650	400	6,8	3,1	16 A, 5 poles	78	1,40	1,95	2,20	1.755	125	12
VA2000	800	400	11,0	5,5	16 A, 5 poles	80	1,40	2,20	2,20	1.800	125	2 x 10
VA2500	900	400	11,0	5,5	16 A, 5 poles	80	1,40	2,20	2,37	1.990	160/ 125	2 x 10